## **AMENDMENTS TO THE CLAIMS**

- 1. (Currently Amended) A portable communication apparatus, comprising:
- a) a main housing having a plurality of first keys and an upper surface provided with a first speaker device;
  - b) a hinge axis extending across the main housing;
- c) a fixed housing affixed to a first peripheral portion of the main housing and having an upper surface provided with a second speaker device, the first peripheral portion being located at one side of the hinge axis; and
- d) a rotational housing rotatable about the hinge axis, the rotational housing being in contact with the fixed housing while surrounding the first peripheral portion of the main housing when the rotational housing is closed on the fixed housing, the rotational housing being most distant from the fixed housing while surrounding a second peripheral portion of the main housing when the rotational housing is completely opened from the fixed housing, the rotational housing having an upper surface provided with a camera lens and a lower surface provided with a third speaker device; and
- e) a battery pack provided on a bottom of the apparatus and including a stylus that is insertable into and withdrawable from the battery pack in a longitudinal direction to the battery pack.
- 2. (Currently Amended) A portable communication apparatus according to claim 1, wherein the main housing has a display and a plurality of first keys, and has a lateral surface provided with at least one second key.
- 3. (Original) A portable communication apparatus according to claim 2, wherein the fixed housing has at least one third key.
- 4. (Currently Amended) A portable communication apparatus according to claim 3, wherein the rotational housing has an upper surface provided with a camera lens and at least one fourth key, and has a lower surface provided with at least one fifth key.

- 5. (Original) A portable communication apparatus according to claim 1, wherein the fixed housing comprises a fixed body and a pair of legs extending from at least two corners of the fixed body in one direction.
- 6. (Previously Presented) A portable communication apparatus according to claim 1, wherein the rotational housing comprises:

a rotational body;

a pair of legs extending from at least two corners of the rotational body in one direction, the pair of legs having an opening formed between them so as to accommodate the main housing, each of the legs having a curved portion; and

a curved portion formed in the pair of legs, wherein a lower surface of the fixed housing is formed on a same line as a lower surface of the rotational housing.

- 7. (Original) A portable communication apparatus according to claim 2, wherein the display is constructed as one unit for representing and inputting information.
- 8. (Original) A portable communication apparatus according to claim 2, wherein the display has a center through which the hinge axis passes.